558715

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 16 December 2004 (16.12.2004)

PCT

(10) International Publication Number WO 2004/109598 A1

(51) International Patent Classification7:

G06T 3/40

(21) International Application Number:

PCT/IB2004/050767

(22) International Filing Date: 25 May 2004 (25.05.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03101617.3


4 June 2003 (04.06.2003)

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): FERRETTI, Giulio [IT/IT]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). CARRAI, Paola [IT/IT]; c/o Prof.

- 6, NL-5656 AA Eindhoven (NL). ZOTTA, Francesco [IT/IT]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). RAMPONI, Giovanni [IT/IT]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agent: GROENENDAAL, Antonius, W., M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: INTERPOLATION OF IMAGES



(57) Abstract: In a method of interpolating sample values (f) of samples (Pi, Pot) of an image, a direction of a local gradient (8) of the sample values (f) for a particular one of the samples (Pi, Pot) is determined (1) from sample values (f) neighboring the particular one of the samples (Pi, Pot). The positions of interpolator input values (ai) are selected (20) in the direction of the local gradient (8) of the particular one of the samples (Pi, Pot). The interpolator input values (ai) for the particular one of the samples (Pi, Pot) are interpolated (21) from pixel values (f) neighboring the interpolator input values (ai). And, a warping factor (A) for a warped distance interpolating (3) is determined (22) using the interpolator input values (ai).

WO 2004/109598 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.